



THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATES INFORMATION WHICH IS PROPRIETARY. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.

SPECIFICATIONS

1. Curb w/integral capflashing- 11 Ga. Aluminium (corners fully welded)
2. Cover - 11 Ga. Aluminium
3. Cover Liner - 18 Ga. Aluminium
4. 50mm Polyisocyanurate Curb Insulation
5. 50mm Polyisocyanurate Cover Insulation
6. EPDM Gasket (all around Cover)
7. Pintle Hinge - Stainless Steel Type 316
8. Bilclip® flashing system
9. Actuator with Carriage - 24VDC (SEE NOTE 1)
10. Junction Box

SHOP FINISH

Aluminium: Mill Finish
Hardware: Corrosion Resistant (unless otherwise specified)

NOTES:

1. The travel of the actuator will pass below the base mounting flange position. Ensure there are no obstructions below.
2. This product is designed to be installed on a flat roof.
3. Full specifications are available on website: www.bilco.com

Customer _____

P.O. No. _____

Job _____

Sales Rep. _____

Bilco® Manufacturers of Doors for Special Services
THE BILCO COMPANY
New Haven, Connecticut 06505

**SINGLE LEAF SMOKE VENT
TYPE ENB-50REM**

| QTY | TYPE | SIZE WIDTH x LENGTH HINGE SIDE |
|-----|-----------|--------------------------------------|
| □ | ENB-50REM | 760mm x 1620mm |

Web Site: www.bilco.com