



SECTION

**SPECIFICATIONS**

1. Curb w/integral capflashing- 11 Ga. Aluminium (corners fully welded)
2. Cover - 11 Ga. Aluminium
3. Cover Liner - 18 Ga. Aluminium
4. 50mm Polyisocyanurate Curb Insulation
5. 50mm Polyisocyanurate Cover Insulation
6. EPDM Gasket (all around Cover)
7. Pintle Hinge - Stainless Steel Type 316
8. Bilclip® flashing system
9. Slam Latch with inside and outside handles w/padlock hasps
10. Lock strike and padlock hasp
11. Lifting mechanism with reinforced composite tubes and electrocoated compression springs
12. Heavy duty hold open arm with red vinyl grip and cover release
13. Arm guide bracket
14. Cover hold chain, (1) @ each end

**SHOP FINISH**

Aluminium: Mill Finish  
 Hardware: Corrosion Resistant (unless otherwise specified)

**NOTES:**

1. This product may be installed on either a flat or sloping roof. When installed on a slope, the hinge side must run parallel with the slope. If slope exceeds 30°, advise factory for modification.
2. Full specifications are available on website: [www.bilco.com](http://www.bilco.com)

Customer \_\_\_\_\_

P.O. No. \_\_\_\_\_

Job \_\_\_\_\_

Sales Rep. \_\_\_\_\_

**Bilco**® Manufacturers of Doors for Special Services  
 THE BILCO COMPANY  
 New Haven, Connecticut 06505

**SINGLE LEAF ROOF ACCESS HATCH  
 TYPE F-50T**

QTY	TYPE	SIZE WIDTH x LENGTH
□	F-50T	1220mm x 1220mm HINGE SIDE

Web Site: [www.bilco.com](http://www.bilco.com)

THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATES INFORMATION WHICH IS PROPRIETARY. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.