



SECTION

SPECIFICATIONS

1. Curb w/ apron – 11 Ga. Aluminium (corners fully welded)
2. Cover – 11 Ga. Aluminium
3. Cover Liner – 18 Ga. Aluminium
4. 25mm Fiberglass Curb Insulation
5. 50mm Polyisocyanurate Cover Insulation
6. EPDM Gasket (all around Cover)
7. Pintle Hinge – Stainless Steel Type 316
8. Anchor Tabs
9. Slam Latch with inside and outside handles w/padlock hasps (Handles to be installed on site by customer)
10. Lock strike and padlock hasp
11. Lifting mechanism with reinforced composite tubes and electrocoated compression springs
12. Automatic hold open arm with red vinyl grip and cover release
13. Arm guide bracket

SHOP FINISH

Aluminium: Mill Finish
 Hardware: Corrosion Resistant (unless otherwise specified)

NOTES:

1. This product may be installed on either a flat or sloping roof. When installed on a slope, the hinge side must run parallel with the slope. If slope exceeds 30°, advise factory for modification.
2. Full specifications are available on website: www.bilco.com

Customer _____

P.O. No. _____

Job _____

Sales Rep. _____

Bilco® Manufacturers of Doors for Special Services
 THE BILCO COMPANY
 New Haven, Connecticut 06505

**SINGLE LEAF ROOF ACCESS HATCH
 TYPE S-50VMT**

QTY	TYPE	SIZE WIDTH x LENGTH HINGE SIDE
□	S-50VMT	915mm x 760mm
Web Site: www.bilco.com		

THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATES INFORMATION WHICH IS PROPRIETARY. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.