



SECTION

SPECIFICATIONS

1. Curb w/integral capflashing- 11 Ga. Aluminium (corners fully welded)
2. Cover - 11 Ga. Aluminium
3. Cover Liner - 18 Ga. Aluminium
4. 50mm Polyisocyanurate Curb Insulation
5. 50mm Polyisocyanurate Cover Insulation
6. EPDM Gasket (all around Cover)
7. Pintle Hinge - Stainless Steel Type 316
8. Bilclip<sup>®</sup> flashing system
9. Slam Latch (2 point) with inside and outside handles w/padlock hasps
10. Lock strike and padlock hasp
11. Lifting mechanism with reinforced composite tubes and electrocoated compression springs
12. Automatic hold open arm with red vinyl grip and cover release
13. Arm guide bracket

SHOP FINISH

Aluminium: Mill Finish  
Hardware: Corrosion Resistant (unless otherwise specified)

NOTES:

1. This product may be installed on either a flat or sloping roof. When installed on a slope, the hinge side must run parallel with the slope. If slope exceeds 30°, advise factory for modification.
2. Full specifications are available on website: [www.bilco.com](http://www.bilco.com)

Customer

P.O. No.

Job

Sales Rep.

**Bilco**<sup>®</sup> Manufacturers of Doors for Special Services  
THE BILCO COMPANY  
New Haven, Connecticut 06505

**SINGLE LEAF ROOF ACCESS HATCH  
TYPE SSY-50T**

QTY	TYPE	SIZE WIDTH x LENGTH
	SSY-50T	760mm x 3360mm HINGE SIDE

Web Site: [www.bilco.com](http://www.bilco.com)

THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATES INFORMATION WHICH IS PROPRIETARY. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.